



# PRODUCT DATA SHEET

## PERMABOND 880

### DESCRIPTION

**Permabond 880** is a ready to use, non-reemulsifiable Vinyl Acetate Polymer emulsion designed to permanently bond new Kooldeck, Stucco, and Portland Cement mixes to any properly prepared concrete type surface. **Permabond 880** can be used as an admixture for Portland Cement mixes.

### COLOR

White

### PACKAGING

1 or 5 gallon buckets.

### COVERAGE

200 to 300 square feet per gallon depending on texture and porosity of substrate.

### PREPARATION

Dust, dirt, grease, wax, oil, and any other foreign material must be removed prior to application. Remove all unsound concrete by mechanical means, then prepare the surface by pressure washing and/or cleaning with a muriatic acid solution. Neutralize the muriatic acid with baking soda and completely and thoroughly wash the deck.

### APPLICATION

After surface has been properly prepared, apply **Permabond 880** over clean damp surface allowing 10-15 minutes for penetration before placing the topping (Note: Some settling of contents may have occurred, stir gently without undue agitation as foaming may result.) Optimum performance is achieved when the topping is applied over tacky **Permabond 880**.

### CLEAN-UP

Tools and any overspray may be washed with water prior to drying. After **Permabond 880** has dried, mechanical means is required for removal.

**C.L. Industries**

P.O. Box 593704 • 8188 South Orange Avenue • Orlando, FL 32859-3704  
407/851.2660 • 800/333.2660 • [www.clindustries.com](http://www.clindustries.com)