

PERMASPRAY SELECT

DESCRIPTION:

PermaSpray Select is a resinated deck system that is spray applied over new or existing concrete surfaces. Available in various colors this product is designed for use on commercial walkways, driveways, pool patios and similar decks.

USES:

- Over new or existing concrete surfaces
- Residential or Commercial
- Interior or Exterior
- Walls or floors

CHARACTERISTICS:

- Available in many colors
- Superior Bonding
- Anti Skid Surface
- Ease of application/minimum down time
- Fast curing/can be walked on in 24 hours
- Freeze resistant

SURFACE PREPARATION:

All decks must be completely free of dirt, oil, grease or other foreign materials. This can be accomplished by acid etching or water blasting. Rinse thoroughly with water, making sure no standing or residue is present.

Make sure all low areas and cracks are filled with PermaSpray Select material (see mixing instructions) and are level with existing surface.

MIXING:

In a clean 5 gallon bucket thoroughly mix 1 50 lb. bag of PermaSpray Select Dry Mix with 1 ½ - 2 gallons of Liquid Resin until free of any lumps. **ONLY MIX AMOUNT OF MATERIAL THAT CAN BE SPRAYED WITHIN 15 MINUTES OF MIXING.** Let mix set for 2 minutes, re-mix again with drill for 1 minute. (If material sets up, you may retemper with PermaSpray Select Liquid Resin).

APPLICATION:

Immediately after mixing, fill hopper with mix and begin spraying, cover approximately 70% of concrete surface. Depending on temperature, substrate or exposure to sun, you can begin to knock down material with trowel as soon as sprayed. Test surface for dryness (surface may be dry in 20-30 minutes). Once surface is dry, lightly scrape to remove any loose material or ridges. Using a roller or airless sprayer, apply two thin coats of Color Coat Select. Make sure to let first coat dry completely.

CURING:

Minimum cure is achieved in 8 hours. Best to keep foot traffic off until next day.

Depending on temperature, allow 2 days for automobile or heavy traffic use.

COVERAGE:

- 1 bag Dry Mix to 1 ½ - 2 gallons of Liquid Resin covers approximately 200-250 square feet.
- One gallon of Color Coat Select covers approximately 100 square feet (one coat).

NOTE: Coverage may vary according to condition and porosity of substrate.

